



SC ARTSERV SRL

Sediu: România, 404407 Cluj Napoca, B-dul Nicolae Titulescu 22/3

Contact:

Tel/Fax: 0364-881.213; Mobil: 0721-128.783, 0771-425.091

E-mail: [office@artservcluj.ro](mailto:office@artservcluj.ro), [artserv@yahoo.com](mailto:artserv@yahoo.com)

<http://www.artservcluj.ro>

### TRANSFORMATOARE HERMETICE IZOLATE RASINA

#### Pierderi standard

Clasa de izolatie 24 kV , 20/0.4 kV, Dyn5 – Dyn11, F/F

<b>Puterea</b>	kVA	160	250	315	400	500	630	800	1000	1250	1600	2000	2500
<b>Frecventa</b>	Hz	50											
<b>Tensiune primara</b>	V	20 000 ± 2x2.5%											
<b>Tensiune secundara</b>	V	400											
<b>Grupul de conexiune</b>		Dyn5 / Dyn11											
<b>Temperatura</b>	°C	100											
<b>Temperatura ambient</b>	°C	-5 / 40											
<b>Po</b>	W	650	880	1000	1200	1350	1650	2000	2300	2700	3100	4000	5000
<b>Psc (75°C)</b>	W	2800	3300	4250	4800	5900	6600	8400	9600	13000	14400	16000	20800
<b>usc</b>	%	6%											
<b>Greutate</b>	kg	950	1000	1200	1350	1500	1800	2100	2500	2900	3550	4300	5250
<b>Lungime</b>	mm	1300	1350	1350	1500	1500	1500	1550	1650	1650	1750	1900	1950
<b>Latime</b>	mm	600	640	750	750	750	850	850	1000	1000	1000	1310	1310
<b>Inaltime</b>	mm	120	126	135	144	156	165	181	189	2030	2200	2270	2350

		0	0	0	0	0	0	0	0				
<b>Ecartament</b>	mm	520	520	670	670	670	670	670	820	820	820	1070	1070
<p>Standarde : CEI14-4,14-8-IEC/EN600076-11-CECELEC HD 538.1 ; Tolerante conform srandarde IEC/EN</p>													